

ENERG 💇 🕮 (IE) енергия · ενεργεια

TIKI

AMS10-16 + SHB10-16



55 °C

35 °C

15 **15**

15






35 dB



61 dB



15



2019

811/2013



ENERG Υ UA EHEPΓИЯ · ενεργεια II (IA)

TIKI

AMS10-16 + SHB10-16















2015





X



A++

Α+

A

B

C

D

E



G

Supplier's name:	TI			
Model:	AMS 10-16			
Temperature application	35	55	°C	
Declared load profile for water				
heating				
Seasonal space heating energy	A+++	A++		
efficiency class, average climate:	ATTT	ATT		
Water heating energy efficiency				
class, average climate:				
Rated heat output, average climate:	14.5	14,0	kW	
Annual energy consumption for	0700	0.404	1-20/1-	
space heating, average climate	6702	8431	kWh	
Annual electricity consumption for			kWh	
water heating, average climate			KVVII	
Seasonal space heating energy	470	404	0/	
efficiency, average climate:	176	134	%	
Water heating energy efficiency,			%	
average climate:			70	
Sound power level LWA indoors	3	35	dB	
Rated heat output, cold climate:	15,0	16,0	kW	
Rated heat output, warm climate:	15,0	15,0	kW	
Annual energy consumption for	10040	13629	kWh	
space heating, cold climate	10040	13029	KVVII	
Annual electricity consumption for			kWh	
water heating, cold climate			KVVII	
Annual energy consumption for	3370	4183	kWh	
space heating, warm climate	3370	4105	KVVII	
Annual electricity consumption for			kWh	
water heating, warm climate		1	1.7711	
Seasonal space heating energy	144	113	%	
efficiency, cold climate:				
Water heating energy efficiency,			%	
cold climate:		4		
Seasonal space heating energy efficiency, warm climate:	235	189	%	
Water heating energy efficiency,				
water fleating energy efficiency, warm climate:			%	
Sound power level LWA outdoors	6	62	dB	

Data for package fiche

Controller class	VI		
Controller contribution to efficiency	4,0		%
Seasonal space heating energy efficiency of package, average climate:	180	138	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A++	%
Seasonal space heating energy efficiency of package, cold climate:	148	117	%
Seasonal space heating energy efficiency of package, warm climate:	239	193	%

AMS 10-16 + SHB10-16		
Air-to-water		
No		
Yes		
Yes		
Average		
Medium temperature (55 °C)		



Temperature application:		Med	dium tem	perature (55 °C)			
Applied standards: EN14825, EN16147	1		1 1	Consend anno hosting anares	1		1
Rated heat output	Prated	14,0	kW	Seasonal space heating energy efficiency	$\eta_{\rm s}$	134	%
		,0		,	10	20.	,,
Declared capacity for part load at outdoor temperature Tj				Declared coefficient of performance for part load at outdoor temperature Tj			
Tj = -7 °C	Pdh	12,5	kW	Tj = -7 °C	COPd	2,01	-
Tj = +2 °C	Pdh	7,6	kW	Tj = +2 °C	COPd	3,29	-
Tj = +7 °C	Pdh	4,9	kW	Tj = +7 °C	COPd	4,68	-
Tj = +12 °C	Pdh	6,8	kW	Tj = +12 °C	COPd	6,51	-
Tj = biv	Pdh	12,7	kW	Tj = biv	COPd	1,95	-
Tj = TOL	Pdh	11,0	kW	Tj = TOL	COPd	1,95	-
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		-
Bivalent temperature	T _{biv}	-7,6	°C	Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych		kW	Cycling interval efficiency	COPcyc		-
Degradation co-efficient	Cdh	0,98	-	Heating water operating limit	WTOL	58	°C
Power consumption in modes other than active	_			Supplementary heater			
Off mode	P _{OFF}	0,002	kW	Rated heat output	Psup	3,0	kW
Thermostat-off mode	P_{TO}	0,016	kW				
Standby mode	P_SB	0,015	kW	Type of energy input	Electric		
Crankcase heater mode	P _{CK}	0,035	kW				
Other items							
Capacity control	Variable			Rated air flow rate, outdoors		6000	m³/h
Sound power level, indoors/outdoors	L _{WA}	35/62	dB	Rated water flow rate, indoor heat exchanger		1,21	m³/h
Annual energy consumption	Q _{HF}	8431	kWh	Rated brine or water flow rate, outdoor heat exchanger			m³/h
For heat pump combination heater:				<u> </u>			<u> </u>
Declared load profile				Water heating energy efficiency	η_{wh}		%
							ı
Daily electricity consumption	Q_{elec}		kWh	Daily fuel consumption	Q_{fuel}		kWh
Annual electricity consumption	AEC		kWh	Annual fuel consumption	AFC		GJ
Approved by:							
Contact details	TIKI HVAC	C d.o.o., Pa	artizansk	a cesta 12, 3320 Velenje, Slovenia			